



Grinder Qwik Lift Station (QLS) SeriesEngineering Designed/Factory Preassembled







Complete preassembled lift stations built to engineering specifications by trained factory experts. Save time, labor and money with a system that works right out of the box.

PICK YOUR GRINDER...





Residential and commercial applications Zoeller's 820 grinder pump pulverizes rags, wipes, and sanitary napkins that might be found in the waste stream.



Zoeller's 840 REVERSING grinder has even more features making it THE grinder pump to use in some of the most extreme applications. Its reversing capability can handle materials such as towels, rags, and other heavy fabrics that can be found in the waste stream.

MODEL **820**

- Hardened stainless steel cutter and disc for superior wear resistance
- Cutting plate decreases solids to less than 1/8" (3mm) which reduces clogging in pump and piping
- Cast iron finned motor housing design for superior motor heat disipitation
- Oil filled motor for cool and long running motor protection
- Baked on electronically charged epoxy coating for rust protection durability in every exterior crevice, for long pump life
- All stainless steel hardware prevents rusting and corrosion
- 36 month limited warranty

MODEL 840


INDUSTRY'S ONLY 2HP REVERSING GRINDER

- Hardened 440C high carbon stainless steel 5-blade cutter for efficient and superior cuts per minute
- Reversing cutter design reverses and automatically alternates directions, extending blade life while eliminating potential material hang ups
- Built in moisture detection probes notifies user of potential seal failures to avoid premature motor failure and costly pump replacement
- Ductile iron impeller protects impeller from cracking due to foreign materials such as rocks and other external debris
- Vortex design provides clear path for solids through volute to prevent clogging
- Dual mechanical shaft seals prevent moisture intrusion into motor chamber
- 18 month limited warranty

OLS SERIES PREFABRICATED LIFT STATIONS WITH Z-RAIL® TECHNOLOGY



- QLS Series® systems are prefabricated including all piping and rail system components.
- ✓ **Z-Rail® System:** Both the disconnect portion and the upper guide rail supports are made of domestic epoxy powder coated ductile iron, providing superior strength. Dual guide rails add stability, ensuring that the pump will not spin on the rail during installation or removal.
- Basin: Zoeller Company stocks many different basin and cover options to fit a multitude of wastewater collection projects. Basin sizes from 24" x 48" to 48" x 120" meet most application needs. Customized packages available.
- **Pipe Seal Hub:** A 4" pipe seal is provided as a convenient field-installed inlet hub.
- ✓ **AFD:** QLS Series® basins come with an anti-floatation collar to resist bouyancy in high groundwater locations.
- Flex-Boot Discharge Connection: A flexible, stable discharge seal remains watertight despite external pressures due to pipe settling.
- Schedule 80 PVC Piping: Schedule 80 PVC discharge piping provides greater support and dependability with its thicker walls and higher pressure rating.



SIMPLEX SYSTEMS		
SYSTEM NUMBER	DESCRIPTION	VOLTAGE/PHASE
ZPS246024BFI820JBX	24x60 2HP Simplex Grinder Lift Station Discharge @ 24"	208 v / 1ph
ZPS246024BFE820JBX	24x60 2HP Simplex Grinder Lift Station Discharge @ 24"	230 v / 1 ph
ZPS249636BFI820JBX	24x60 2HP Simplex Grinder Lift Station Discharge @ 36"	208 v / 1 ph
ZPS249636BFE820JBX	24x60 2HP Simplex Grinder Lift Station Discharge @ 36"	230 v / 1 ph
ZPS309636BFI820JBX	30x96 2HP Simplex Grinder Lift Station Discharge @ 36"	208 v / 1 ph
ZPS309636BFE820JBX	30x96 2HP Simplex Grinder Lift Station Discharge @ 36"	230 v / 1 ph
	DUPLEX SYSTEMS	
ZPD364819BEI820JBX	36x48 2HP Duplex Grinder Lift Station Discharge @ 19"	208 v / 1 ph
ZPD364819BEE820JBX	36x48 2HP Duplex Grinder Lift Station Discharge @ 19"	230 v / 1 ph
ZPD366024BFI820JBX	36x60 2HP Duplex Grinder Lift Station Discharge @ 24"	208 v / 1 ph
ZPD366024BFE820JBX	36x60 2HP Duplex Grinder Lift Station Discharge @ 24"	230 v / 1 ph
ZPD368424BFI820JBX	36x84 2HP Duplex Grinder Lift Station Discharge @ 24"	208 v / 1 ph
ZPD368424BFE820JBX	36x84 2HP Duplex Grinder Lift Station Discharge @ 24"	230 v / 1 ph
Comple	ete Preassembled 840 REVERSING 2HP Grinde	r QLS System
	SIMPLEX SYSTEMS	
SYSTEM NUMBER	DESCRIPTION	VOLTAGE/PHASE
ZPS246024BFI840JBX	24x60 2HP Simplex Grinder Lift Station Discharge @ 24"	208 v / 1 ph
ZPS246024BFE840JBX	24x60 2HP Simplex Grinder Lift Station Discharge @ 24"	230 v / 1 ph
ZPS249636BFI840JBX	24x60 2HP Simplex Grinder Lift Station Discharge @ 36"	208 v / 1 ph
ZPS249636BFE840JBX	24x60 2HP Simplex Grinder Lift Station Discharge @ 36"	230 v / 1 ph
ZPS309636BFI840JBX	30x96 2HP Simplex Grinder Lift Station Discharge @ 36"	208 v / 1 ph
ZPS309636BFE840JBX	30x96 2HP Simplex Grinder Lift Station Discharge @ 36"	230 v / 1 ph
	DUPLEX SYSTEMS	
ZPD364819BEI840JBX	36x48 2HP Duplex Grinder Lift Station Discharge @ 19"	208 v / 1 ph
ZPD364819BEE840JBX	36x48 2HP Duplex Grinder Lift Station Discharge @ 19"	230 v / 1 ph
ZPD366024BFI840JBX	36x60 2HP Duplex Grinder Lift Station Discharge @ 24"	208 v / 1 ph
ZPD366024BFE840JBX	36x60 2HP Duplex Grinder Lift Station Discharge @ 24"	230 v / 1 ph
ZPD368424BFI840JBX	36x84 2HP Duplex Grinder Lift Station Discharge @ 24"	208 v / 1 ph

ZPD368424BFE840JBX

Add An Extension
For applications that require a deeper install, Zoeller recommends that the right size basin be ordered. However, for a quick and efficient option for units already in stock or for systems already ordered, Zoeller does offer a set of extensions that can be installed in order to properly bury the basin to grade.

36x84 2HP Duplex Grinder Lift Station Discharge @ 24"



Part Number	Description
31-0994	12" Fiberglass Extension for 24" Basin
31-0954	24" Fiberglass Extension for 24" Basin
31-2155	12" Fiberglass Extension for 30" Basin
31-0555	24" Fiberglass Extension for 30" Basin
31-0813	12" Fiberglass Extension for 36" Basin
31-0399	24" Fiberglass Extension for 36" Basin

EXTENSIONS

230 v / 1 ph